

2T-versionGeneral Information



2T-version

General Information



Introduction

- 2T-variant: split temperature zones separated by directed air flow, Fresh food / snack
 - Approx. + 10 15 °C on the upper shelves
 - Food-safety storage at ≤ + 4 °C on the lower shelves (LM zone)
- The temperature separation position can be adjusted within a pre-defined range.
- The Food safety software monitors the temperature in the LM-zone and ensures that only properly chilled products are dispensed



Overview

Dimensions: 1,830 x 880 x 840 mm (height x width x depth)*

Weight: approx. 265 kg (without products, depending on the layout)

Electrical connection values: 220- 230 V / 50/60 Hz / min. 10 A

Power consumption: 400 W (varies depending on the type of chiller unit)

*Deviations in the housing dimensions are possible due to add-on parts and accessories.

Design variants

Operator panel

- EB = Operator panel made from stainless steel
- RB = Operator panel RAL painted

Cabinet colours

■ Pure white (RAL 9010)

2T-versionGeneral Information



- White aluminum (RAL 9006)
- Jet black (RAL 9005)

Options and accessories

- Metal keypad
- Coin insert slide and coin return drum
- Locking lever protection
- Light barrier
- LM variant
- 2T variant
- Reinforced shelves (lower 3 shelves)



Sielaff GmbH & Co. KG Automatenbau Herrieden Münchener Str. 20 91567 Herrieden Germany

Phone: +49 9825 18-0 Telefax: +49 9825 18-311155

info@sielaff.de www.sielaff.com See here for our company profile video



