

MonoSort Basic



MonoSort

Basic



Features

- Space-saving, high-performance sorting solution for medium to large volumes
- One compactor per housing ensures a fast and reliable flow rate with up to 60 containers/minute
- Material separation possible with up to 5 housings and/or inside housings
- Full-round system guarantees continuous operation, even when the container is emptied - for a non-stop coin return
- Plug-and-Play technology enables simple and costefficient installation and set-up
- Easy access and flexible removal direction, either right or left
- The unique FlexiSort conveyor belt makes it possible to transport almost any form and shape
- Flipper the deflector with directly driven belt ensures the correct positioning of bottles, cans and beverage cartons



SiVario 2020 Basic data

Dimensions: 1,715 x 600 x 1,080 mm (height x width x depth)*

Weight: Approx. 330 kg

Electrical connection values: 3L/N/PE, 400 V, 50 Hz

Power consumption: Max. 650 W, 70 W Standby

Operating temperature: +5 °C to +40 °C

non-condensing

Wall opening: 1,750 x 650 mm (height x width)

*Deviations in the housing dimensions are possible due to add-on parts and accessories.

MonoSort Basic



Housing

Housings: • 1 compactor per housing

• Up to 5 housings possible

• 90° deflection of container is possible

Capacity per enclosure: • approx. 650 PET bottles

• approx. 1,500 cans or

• approx. 1,200 glass bottles

Dimensions: 1,750 x 910 x 1,350 mm (height x width x depth)*

Weight: • approx. 290 kg (PET/cans)

• approx. 260 kg (glass)

Electrical connection values: 3L/N/PE, 400 V, 50 Hz

Power consumption: • PET: Max. 2,000 W (housing)

· Glass: Max. 1,200 W (housing)

· Standby: 10 W

Container for empties

■ Size: Euro pallet with 975 mm x 800 mm x 1,200 mm (height x width x depth)

Conformity

- CE, DPG-certified
- UKCA (UK Conformity Assessed)

Material separation

■ Segregated collection according to material type is possible

^{*}Deviations in the housing dimensions are possible due to add-on parts and accessories.



Sielaff GmbH & Co. KG Automatenbau Herrieden Münchener Str. 20 91567 Herrieden Germany

Phone: +49 9825 18-0 Telefax: +49 9825 18-311155

info@sielaff.de www.sielaff.com See here for our company profile video



