



SiLine[®] GF L RO
General information



Introduction

- Protection class: IP24
- Winter resistant up to -20°C
- Rain roof and weatherproof protection
- Impact protection (Standard 12 mm PC)
- Laminated safety glass with UV-light filter (ESG safety glass)
- Reinforced wavy locking lever protection (5 mm stainless steel), the wavy profile prevents prising or lifting
- Coin insert slide and coin return drum
- High security frame with side lock and CES mortice lock (KESO as an option)
- Residual current circuit breaker
- Chiller unit with heater ("Frost monitoring function", which keeps the internal temperature above 0 °C)
- Rear wall (Branding opportunity)



Overview

Dimensions:	1,866 x 1,210 x 1,000 mm (height x width x depth)*
Weight:	approx. 480 kg
Electrical connection values:	220 – 230 V / 50 Hz / min. 10 A
Power consumption:	750 W

**Deviations in the housing dimensions are possible due to add-on parts and accessories.*

Design variants

Design panel

- Design VA = Lower design panel made from Stainless
- Design RA = Lower design panel RAL painted

Cabinet colours

- Pure white (RAL 9010)

- White aluminum (RAL 9006)
- Jet black (RAL 9005)

Optional:

The standard design VA can be added with the design package A or B.
Design RA can be complemented with Design package A.

Design package A includes:

- LED-Decoration strips above and below the glass panel

Design package B includes:

- LED-Decoration strips above and below the glass panel
- Upper door decoration panel in stainless steel
- Kickplate in stainless steel

All design variants can be found in the brochure.

An overview of the benefits:

- Anti-vandalism panel
- Rain shield and weatherproof protection
- Coin insert slide and coin return drum
- Reinforced locking lever protection
- Security frame with side lock
- Laminated safety glass panel with UV filter
- Residual current circuit breaker
- High performance chiller unit with heater with "frost monitoring function", so that the internal temperature is held above 0°C
- Rear panel offers advertising opportunity
- KESO

Optional

- Impact protection made of 8 mm thick laminated safety glass instead of 12mm PC



Sielaff GmbH & Co. KG
Automatenbau Herrieden
Münchener Str. 20
91567 Herrieden
Germany

Phone: +49 9825 18-0
Telefax: +49 9825 18-311155
info@sielaff.de
www.sielaff.com

See here for our
company profile video



■ MADE
■ IN
■ GERMANY