



# SiVend® HG Outdoor Basic



# SiVend® HG Outdoor Basic

■ MADE  
■ IN  
■ GERMANY

## General facts

- Outdoor version only in RAL 9005
- 70 mm or 80 mm cup dispenser
- Insulated housing:  
Side, base and rear panels are insulated with 34 mm of polyurethane foam
- Rear panel and rain canopy made from painted steel
- Front, side and rear trim
- Floor mounting kit
- Dispense outlet lock/shutter above the dispense outlet to prevent access to the vending machine
- Integrated heating with 250 W to keep the interior frost-free
- Tried and tested. Sielaff anti-theft protection frame with side lock
- Reinforced locking lever protection
- Weather- and vandalism-resistant
- IP24 protection class
- Ambient temperature of approximately -15 °C to +32 °C
- Max. power consumption 3.15



## Basic data

Dimensions:	1,856.5 x 763 x 846 mm (height x width x depth)*
Weight:	Approx. 240 kg (depending on the variant)
Cup output:	up to 140 cups/hour (depending upon product and settings)
Electrical Data:	220 – 230 V / 50/60 Hz / 16 A
Power Input:	3,15 kW
Water Connection:	3/8" internal screw thread

\* Machine dimensions may vary due to add-on parts and accessories

## Design variants

### Housing colors

- Pure white (RAL 9010)
- White aluminum (RAL 9006)
- Deep black (RAL 9005)

# SiVend<sup>®</sup> HG Outdoor Basic

MADE  
IN  
GERMANY

## Door colors

- Pure white (RAL 9010)
- White aluminum (RAL 9006)
- Deep black (RAL 9005)

## Designs

- Design A (Standard)
- Design B
- Design C

All pictures relating to the design variants can be found in the brochure.



Sielaff GmbH & Co. KG  
Automatenbau Herrieden  
Münchener Str. 20  
91567 Herrieden  
Germany

Phone: +49 9825 18-0  
Telefax: +49 9825 18-311155  
[info@sielaff.de](mailto:info@sielaff.de)  
[www.sielaff.com](http://www.sielaff.com)

See here for our  
company profile video



■ MADE  
■ IN  
■ GERMANY