



**Coffee pleasure  
whatever the weather**

SiVend HG Outdoor



# Benefit from our strengths

## Coffee pleasure whatever the weather.

Sielaff guarantees the finest coffee served from a vending machine. The components used by Sielaff, including the brewer unit and high-performance grinder, are the foundations for maximum operational reliability.

The hot drinks machine is perfectly designed for outdoors. The side and lower panels and the rear wall of the housing are perfectly insulated with 34 mm polyurethane foam.

The SiVend HG Outdoor performs reliably at ambient temperatures ranging from approximately -15°C to +32°C, ensuring safe and smooth operation in almost any weather conditions.

## Robust, safe and reliable. Just coffee. No compromises.

The SiVend HG CVS RO and CIS RO were specially developed for the rigours of outdoor use and are genuine eye-catchers with their sophisticated technology and maximum durability.

Thanks to its IP24 rating, the vending machine is resistant to water splashes, ensuring that is always available for use.

An integrated rain canopy and an additional cover over the drinks outlet provide even more protection from inclement weather.

The vending machine also raises the bar for safety: a sturdy anti-theft protection frame with integrated side lock to effectively protect the inner workings from unauthorised access. The coin chute with return drum ensures smooth and secure payment processing in day-to-day operations.

With additionally reinforced locking lever protection, the vending machine is able to withstand vandalism and forced opening – maximising security at publicly accessible locations.

The practical shutter system on the drinks dispenser provides added benefits and protection, whilst the sturdy rear panel and the option to securely fix the machine to the floor ensures safety and stability – even in busy locations..

On the inside, built-in heating keeps the unit running smoothly even at low temperatures, whilst the RCD meets even the most rigorous safety standards.

The result: an outdoor hot drinks machine which not only serves excellent coffee, but also demonstrates exceptional reliability and safety – 24/7, all year round.



*Perfectly and individually tailored to different requirements*



*Unbeatable outdoor enjoyment on sunny days for meeting up in the park*



*The excellent coffee quality and wide variety of products are second to none*

### Easy transport – simple commissioning.

Delivered by pallet truck, the standalone vending machines can be positioned using their own height-adjustable feet – ready to generate sales almost immediately.

### Success at any location.

Thanks to our well-designed, low maintenance operation, profitability is guaranteed wherever you install the vending machine.

### RB design variant – simple operation.

The stylish RB design with operating panel to match the door colour (RAL) is a genuine eye-catcher at any location – including 14 illuminated direct selection buttons made of metal.

### Pleasure begins with attention to detail.

Sielaff perfectly composes the right recipe to accommodate each and every taste. To consistently meet the highest demands of your customers – from latte macchiato to the legendary Viennese melange.

The attractive look, simple, ergonomic operation and the high standard of hygiene of our hot drinks machines cannot fail to appeal in the vending sector and ensure sustainable vending success.



### General facts SiVend CVS / CIS Outdoor

- Outdoor version only in RAL 9005
- 70 mm or 80 mm cup dispenser
- Insulated housing:
  - Side, base and rear panels are insulated with 34 mm of polyurethane foam
- Rear panel and rain canopy made from painted steel
- Front, side and rear trim
- Floor mounting kit
- Dispense outlet lock/shutter above the dispense outlet to prevent access to the vending machine
- Integrated heating with 250 W to keep the interior frost-free
- Tried and tested. Sielaff anti-theft protection frame with side lock
- Reinforced locking lever protection
- Weather- and vandalism-resistant
- IP24 protection class
- Ambient temperature of approximately -15 °C to +32 °C
- Max. power consumption 3.15 kW
- On-site fuse protection 16 A

# Talent and Technology

## General information

- Standard designs, with optional customised advertising panel
- Easy integration of different payment systems
- Controls positioned at an ergonomically accessible height
- Modular design – recyclable and easy to service

## Housing

- Internal parts made of powder-coated metal or from stainless steel, plastic decor parts with two-component coating
- Internal illumination with door contact switch
- Service socket

## Technology

- Hose clamping valves with platinum-cured hoses
- Lockable product chutes made from antistatic material
- Swivel arm for product dispense
- Light barrier for cup/container detection
- Hot water circulation up to the valve
- Optional: Pot switching

## Dosing

- 50 freely programmable beverage recipes
- Freely adjustable beverage volume up to 300 ml per serving
- Freely-adjustable mixer speed for each beverage (up to 17,000 rpm)
- Freely-programmable torque and runtime of dosing motors
- Strong product foaming
- Time-controlled locking of individual products possible
- Hot water dispensing possible

## Vending/service data

- Logging according to the EVA-DTS standard
- Data transfer with mobile data acquisition device (IR interface)
- Telemetry connection possible
- Sielector for configuration and statistical readout from the vending machine

## Performance data

- Dispenses approx. 140 cups per hour
- Suitable for cup sizes up to 300 ml

## Maintenance

- Quick and easy to perform with low effort and cost
- Full service after 12 months / 40,000 portions
- Interim service after 6 months / 20,000 portions
  - mixer blade
  - gasket for mixer flange
  - silicone flow regulating disc



*Attractive design and build-quality of this fully automatic machine enable it to cope with 24/7 outdoor vending.*


# Variants

## CIS

Don't let your "me time" pass you by without your favourite hot drink. The CIS instant version can provide you with a whole host of delicious beverages. Alongside its attractive design there is reliability, operator-friendliness and ease of servicing. At the touch of a button customers can serve themselves to a delicious hot, speciality drink.

## Technology in the instant zone

- Peristaltic pump for high-level dosing accuracy and scale prevention
- Hose clamping valves with platinum-cured hoses
- Freely-adjustable mixer speed for each beverage (up to 17,000 rpm)
- Boiler heating: 2.8 kW
- Boiler volume: 3l
- 7 instant product containers and 4 mixers create the right blend and add plenty of variety to the range




Variant 7401  
7 product containers,  
4 mixer units

## CVS

The CVS offers a combination of freshly ground whole beans and instant products to deliver a taste experience. The high-tech PEEK -brewer and "Made in Germany" technology are synonymous with reliability and coffee culture at the highest level. Whether a typical espresso with perfect crema, cappuccino or trendy speciality coffees such as latte macchiato – the machine delivers every drink to connoisseur quality.

The versatility of the CVS as well as the quality and design of this fully automatic vending machine, enables it to cope with diverse requirements of any location.



Variant 6402  
1 large bean container  
6 instant product containers,  
4 mixer units

## Technology in the espresso zone

- High-tech peek brewer for coffee servings from 6 –14 g
- High performance horizontal grinder: Grinder with tempered steel discs with 65 mm diameter
- Bean container with a capacity of 4.5 kg
- Boiler heating:  
Espresso boiler 2.7 kW  
Instant boiler 2.8 kW
- Boiler volume:  
Instant 3 l, espresso 0.5 l



Can be customised thanks to the wide range of variants



High-quality components from the HoReCa range

# Variants

Approx. container width	67 mm	78 mm	137 mm
Approx. container volume	4,900 ccm	5,800 ccm	10,000 ccm
Instant coffee	1,000 g	1,250 g	-
Sugar	4,000 g	5,000 g	-
Whitener / Topping	2,500 g	3,000 g	-
Chocolate	-	3,500 g	6,000 g
Tea	4,500 g	5,500 g	-
Soup	3,500 g	4,500 g	-
Special Cappuccino	2,500 g	3,000 g	5,000 g
Bean coffee	4,500 g bean hopper		

## Cup dispenser

The pre-configured cup catcher in the cup dispense chute improves the smooth dispensing process by holding the cups securely to prevent jams..

- BAM Cup dispense technology from Sielaff
- Capacity of up to 500 cups
- Suitable for numerous cup types with a diameter of 70 and 80 mm

Designed according to sustainability and environmental principles, you can select the cup for dispensing and then use a to-go container instead.

Smart technology makes a difference – especially when it is from Sielaff.

## Design variants:



CIS/ CVS 500 RB RO  
Design A



CIS/ CVS 500 RB RO  
Design B



CIS/ CVS 500 RB RO  
Design C



Housing and door available in jet black (RAL 9005), white aluminium (RAL 9006) and pure white (RAL 9010)

\* Machine dimensions may vary due to add-on parts and accessories



#### Dimensions (with anti-theft protection frame and rain canopy)

- 1,856.5 x 763 x 846 mm  
(height x width x depth)\*

#### Weight

- Approx. 240 kg  
(depending on the variant)

#### Cup output

- up to 140 cups/hour (depending upon product and settings)

#### Electrical Data

- 220–230 V/50/60 Hz/16 A

#### Power Input

- 3.15 kW

#### Water Connection

- 3/8" internal screw thread



Sielaff GmbH & Co. KG  
Automatenbau Herrieden  
Münchener Str. 20  
91567 Herrieden  
Germany

Telephone: +49 9825 18-0  
export@sielaff.de  
www.sielaff.com

Sielaff UK Ltd.  
Unit 1, South Staffs Freight  
Terminal, Lynn Lane  
Shenstone Lichfield WS14 0ED  
Great Britain

Telephone: +44 1543 48-4333  
info@sielaff.co.uk  
www.sielaff.com

**Scan here for our  
company profile video**

