



TECHNICAL INFORMATION

Date: 06.03.2023
TI: 0223
Machine type/s: SÜ SiLine; GF SiLine; HG SiLine; RN SiLine SiOne;

SiLine Software 0.18.0

The latest, improved SiLine Software 0.18.0 SiLine software boasts new functions. Here are a few of its new main features. The functions listed below apply to all SiLine machines:

Cleaning

Screen cleaning has been enhanced. In particular the duration when the touchscreen is deactivated can be programmed to between 0 and 200 seconds in the machine configuration.

Telemetry

The configuration of the LTE-modem TRB140 made by Teltonika (Sielaff part number: 8670766000) has been programmed in the software so that it can be used without having to make additional adjustments.

Time and date

Under network settings a (time server) NTP and a DNS-server can be configured, in order to retrieve date and time online. If an NTP-server is active the time and date can no longer be manually adjusted in the time settings.

If no time server is available, depending on the network configuration an NTP-Pool, such as <https://www.ntppool.org/> can be used. Please observe any usage requirements relating to the NTP-driver as well as the availability of an internet connection.

REST-API

The following commands have been added to the REST-API:

restartprocessesGet	Restart all machine processes.
rebootGet	Restart the complete machine.

By doing so the machine or more specifically its processes can be restarted using remote connection via REST-API.

SÜ SiLine

The functions listed below apply to all SÜ SiLine machines.

Public mode has been redesigned. It is no longer necessary to programme this separately as it is automatically activated, if in the machine configuration under "selection type" the value "external security selection" is chosen.

SÜ SiLine with Lift

Activating the slam lock on machines with a lift has been improved.

When the lift is blocked an alternative motor will attempt to run. Only if all alternative motors are unable to run, the sale will be aborted and a reference run triggered.

The software assists the new belt drive on the lift (SÜ SiLine Typ 04).



GF SiLine

The functions listed below apply to all GF SiLinemachines.

In order to avoid chiller failure the chiller status is periodically checked and if necessary the chiller unit is re-activated.

RN SiLine

The functions listed below apply to all RN SiLinemachines.

In the "Hopper Menu" there is the option to empty both hoppers. Either only one coin can be dispensed or the total contents.

The acceptance procedure has been redesigned.

The service menu has been revised.

Download

The latest software can be found on our Homepage in the [Download-Center](#).

Machine	Current software version	Ex works from serial number
SÜ SiLine S	0.18.0	90539754
SÜ SiLine M	0.18.0	90539772
SÜ SiLine Lift M	0.18.0	90539751
GF SiLine	0.18.0	90539750
RN SiLine	0.18.0	-

Sielaff GmbH & Co. KG Automatenbau Herrieden